

# WeatherStation® Multisensors

A Compact, Rugged Instrument for Informed Decision-Making



## Ultrasonic Instruments

Rugged Reliability,  
Proven Performance.

The Airmar WeatherStation Instruments are unique, as they are the only weather monitoring system that can report Dynamic True and Apparent wind speed and direction/angle in one compact housing with no moving parts or external interfaces.



**Ultrasonic Wind Measurement**  
Dynamic True and Apparent wind speed and direction with no moving parts



**Relative Humidity (optional)**  
Field serviceable RH sensor with calculated dew point



**Rain Measurement**  
Maintenance free acoustic rain measurement including duration, intensity and amount with 95% accuracy



**Barometric Pressure**  
Accurate atmospheric pressure measurement



**10 Hz GPS**  
Position, COG, SOG, time stamping



**Solar Stabilization**  
Solar radiation shield increases the accuracy and stability of temperature and relative humidity readings



**Temperature**  
With calculated heat index and wind chill when RH module is installed



**3-Axis Compass**  
With dynamic stabilization and better than 1° accuracy



**3-Axis Rate Gyro**  
For rate-of-turn data



	110WX	200WX	200WX-IPX7	220WXH	150WXS	150WXS
Apparent wind speed and angle	✓	✓	✓	✓	✓	✓
Dynamic True wind speed and direction		✓	✓	✓	✓	✓
Barometric pressure	✓	✓	✓	✓	✓	✓
Air temperature	✓	✓	✓	✓	✓	✓
10 Hz GPS (Position, COG, SOG)		✓	✓	✓	✓	✓
Three-axis accelerometer for pitch & roll		✓	✓	✓	✓	✓
Two-axis solid-state compass: Better than 1° static compass accuracy					✓	
Three-axis solid-state compass with dynamic stabilization: Better than 1° static compass accuracy Best-in-class 2° dynamic compass accuracy		✓	✓	✓		✓
Three-axis rate gyros provide rate-of-turn data		✓	✓	✓		✓
Solar shield					✓	✓
Rain accumulation, duration, intensity						✓
Heater				✓		
Relative humidity (field-serviceable ) Calculated dew point Calculated heat index	✓ Optional	✓ Optional			✓ Standard	✓ Standard
Weatherproof rating	IPX6*	IPX6*	IPX7	IPX6	IPX4	IPX4
Operating voltage	9-40 VDC	9-40 VDC	9-40 VDC	12-24 VDC	9-40 VDC	9-40 VDC
Output options include: Hardware Interfaces: Serial RS232, Serial RS422, CAN Protocols: NMEA 0183, NMEA 2000® Serial Data Transmission Code: ASCII	✓	✓	✓	✓ (0183 only)	✓	✓

\* Rating stated is without optional RH sensor installed.



[WEATHERSTATIONWX.COM](http://WEATHERSTATIONWX.COM)



An Amphenol Company